

**ICNEE 2011**

2011 International Conference on Network and Electronics Engineering

September, 2011

Singapore



Azad University, Mashhad Branch, Iran

# OFFLINE SIGNATURE RECOGNITION USING MODULAR NEURAL NETWORKS WITH FUZZY RESPONSE INTEGRATION

**Authors:**

Omid Mirzaei, Hassan Irani, Hamid Reza Pourreza

September, 2011

# OUTLINE



- Introduction
- Problem Statement
- The Proposed Method
- Edge Detection
- Curvelet Transform
- Hough Transform
- Mamdani Fuzzy Inference System
- Experimental Results
- Conclusion
- References

# INTRODUCTION




- Developing biometric recognition systems for security and identity verification purposes is very active area of research nowadays [1].
- Among all biometric features, the handwritten signatures are one of the most popular and reliable ones.
- There are two main methods for signature recognition:
  - Online Methods
  - Offline Methods

# PROBLEM STATEMENT




- The problem is concerned with the automatic recognition of a person's signature that is captured on a paper of size 460\*792 and is stored in PC.
- We have a set of N different people, and each has a unique personal signature but can have different samples of that unique one.



# THE PROPOSED METHOD

- The system proposed in this paper consists of a modular neural network with 3 separate modules.



- Each module is given as input the features extracted with different feature extraction methods:
  - Edge Detection
  - Curvelet Transform
  - Hough Transform

# EDGE DETECTION

- For images of handwritten signature, the edges can capture much of the overall structure present within, because people normally write using a single color on a white background.
- We have chosen Canny Edge Detector for our system.



# CURVELET TRANSFORM




- Curvelet can capture the intrinsic geometrical structures such as smooth contours in natural images.
- Curvelets can represent a smooth contour with fewer coefficients.
- The curvelet transform is implemented by decomposing the image into a series of disjoint scales.

# HOUGH TRANSFORM




- The Hough transform can extract line segments from the image.
- In order to reduce the size of the matrix, and the size of the corresponding ANN, the information of the Hough matrix are compressed by 25%.



# MAMDANI FUZZY INFERENCE SYSTEM

FUZZY IF-THEN RULES FOR THE PROPOSED SYSTEM

Rules	Edge Detection	Curvelet Transform	Hough Transform	Decision
1	A	A	A	A
2	A	A	B	A
3	A	A	C	A
4	A	B	A	A
5	A	B	B	B
6	A	B	C	B
7	A	C	A	A
8	A	C	B	C
9	A	C	C	C
10	B	A	A	A
11	B	A	B	B
12	B	A	C	A
13	B	B	A	B
14	B	B	B	B
15	B	B	C	B
16	B	C	A	C
17	B	C	B	B
18	B	C	C	C
19	C	A	A	A
20	C	A	B	A
21	C	A	C	C
22	C	B	A	B
23	C	B	B	B
24	C	B	C	C
25	C	C	A	C
26	C	C	B	C
27	C	C	C	C



# EXPERIMENTAL RESULTS (1/3)



- A data base of images with the signature of 30 people has been built and 9 samples of the signature from each person has been collected: This gives a total of 270 images.



## EXPERIMENTAL RESULTS (2/3)



- In order to obtain comparative measures we divide our experiments into two separate tests:
  - First, we use each module as a monolithic ANN for signature recognition.
  - Second, we train our MNN using all three modules concurrently and the Mamdani fuzzy integral as our integration method.
- In all tests, 210 images were chosen randomly and used for training, and the remaining 60 were used for testing.

## EXPERIMENTAL RESULTS (3/3)



- The ANNs were trained with the Scaled Conjugate Gradient (Trainscg) algorithm, with a goal error of 0.001.
- Moreover, all networks had the same basic ANN architecture, with two hidden layers.


THE BEST RESULTS OBTAINED FOR MONOLITHIC ANNs VS. OUR MODULAR NEURAL NETWORK

Feature Type	Epochs	Neurons	Time	Correct	Accuracy (%)
edge detection	142	100-80	00:00:44	50/60	83.3
curvelet transform	137	100-80	00:00:10	56/60	93.3
Hough transform	139	100-80	00:01:50	54/60	90
modular neural network	-	-	-	58/60	96.6

# CONCLUSION



- The modular approach always outperforms, with varying degrees, the monolithic ANNs.
- The results also show that even with the simple image features used in this work, each of the ANN modules is indeed capable of learning very good discriminating functions.



# REFERENCES (1/2)



- [1] D. Zhang (2000) Automated biometrics technologies and systems. Hong Kong Polytechnic University Ed. Kluwer Academic publishers Chapter 10: 203-206
- [2] N. Papunzarkos, and H. Baltzakis, Off-line signature verification using multiple neural network classification structures, IEEE conferences, 1977
- [3] T. Kaewkongka, K. Chamnongthai, B. Thipakom, Off-Line Signature Recognition Using Parameterized Hough Transform , Fifth International Symposium on Signal Processing and its Applications, ISSPA ,99, Brisbane, Australia, 22-25 August, 1999
- [4] W. Hou, X. Ye and K. Wang, A Survey of Offline Signature Verification, Proceedings of the 2004 International Conference on intelligent Mechatronics and Automation hengdu, China August 2004
- [5] E. Cand Cand`es and D. Donoho, Curvelets: A Surprisingly Effective Nonadaptive Representation of Objects with Edges, Curves and Surface, Vanderbilt University Press, Nashville, TN sity TN, pp. 123–143, 1999
- [6] A. Pérez-Hernández, A. Sánchez and J.F. Vélez, Simplified Stroke-based Approach for Off-line Signature Recognition, 2004
- [7] K. Kalera Meenakshi, Offline Signature Verification and Identification Using Distance Statistics, International Journal of Pattern Recognition and Artificial Intelligence, Vol. 18, No. 7 ,2004
- [8] P. Melin, O. Castillo (2005) Hybrid intelligent systems for pattern recognition using soft computing. An Evolutionary Approach for Neural Networks and Fuzzy Systems (Studies in Fuzziness and Soft Computing) Ed. Springer

# REFERENCES (2/2)



- [9] P. Melin, O. Castillo (2005) Hybrid intelligent systems for pattern recognition. Ed. Springer-Verlag
- [10] P. Melin, C. Gonzalez, D. Bravo, F. Gonzalez, G. Martinez (2007) Modular neural networks and fuzzy Sugeno integral for pattern recognition. Then Case of Human Face and Fingerprint Tijuana Institute of Technology Tijuana Mexico Ed. Springer
- [11] M. Beltr'an, P. Melin, L. Trujillo (2009) Development of Modular Neural Networks with Fuzzy Logic Response Integration for Signature Recognition
- [12] G. Joutel, V. Eglin, S. Bres, H.t Emptoz, Curvelets based Feature Extraction of Handwritten Shapes for Ancient Manuscripts Classification , Proc. of SPIE-IS&T Electronic Imaging, SPIE Vol. 6500, 2007
- [13] F. M. Kazemi, S. Samadi, H. Pourreza, Mo. R. Akbarzadeh, Vehicle Recognition Based on Fourier, Wavelet and Curvelet Transforms – a Comparative Study, IJCSNS International Journal of Computer Science and Network Security, VOL.7 No.2, February 2007
- [14] M. Choi, Y. Jim, M.R. Nam, H.O. Kim, Fusion of Multispectral and Panchromatic Satellite Image Using the Curvelet Transform, IEEE geosciences and remote sensing letters, VOL. 2, No.2, APRIL, 2005

# QUESTIONS



Thanks For Your Attention!